PathRelativePathTo

The destination string buffer must be long enough to hold the return file path

Sean Barnum, Cigital, Inc. [vita¹]

Copyright © 2007 Cigital, Inc.

2007-04-02

Part "Original Cigital Coding Rule in XML"

Mime-type: text/xml, size: 4617 bytes

Attack Category	Malicious Input			
Vulnerability Category	ty Category • Buffer Overflow			
	Unconditional			
Software Context	File Path Management			
Location	• shlwapi.h			
Description	The destination string buffer for the PathRelativePathTo() function must be long enough to hold the return file path.			
	The function PathRelativePathTo() function takes a pair of paths and generates a relative path from one to the other. This could, in theory, be the entirety of one input string, plus "\" units for each directory in the other input string.			
	It is undefined what will occur if both the paths are MAX_PATH in length and have nothing in common, or even worse if the "from" path contains many single character directory names causing each of them to expand to two characters (""). This leaves the potential for returned paths of an unknown state and content.			
APIs	Function Name	Comme	ents	
	PathRelativePathTo			
	PathRelativePathToA	ANSII	implementation	
	PathRelativePathToW	Unicod	e implementation	
Method of Attack	the resulting path could purposely provides long	If the two paths are long and have little in common, the resulting path could be quite large. If the attacker purposely provides long path names, he could overrun a buffer that is not at least MAX_PATH in size.		
Exception Criteria				
Solutions	Solution Solut Applicability Descri	ion ription	Solution Efficacy	

 $^{1. \}quad http://buildsecurityin.us-cert.gov/bsi/about_us/authors/35-BSI.html~(Barnum, Sean)\\$

PathRelativePathTo 1

	Whenever PathRelativePath Pathmeter, is called. DathRelativePath Pathmeter, pszPath, must be at least MAX_PATH characters in length. Effective.		
Signature Details	BOOL PathRelativePathTo(LPTSTR pszPath, LPCTSTR pszFrom, DWORD dwAttrFrom, LPCTSTR pszTo, DWORD dwAttrTo);		
Examples of Incorrect Code	<pre>TCHAR szOut[10] = TEXT(""); // Buffer is too small TCHAR szFrom[] = TEXT("c:\\a\\b\\path"); TCHAR szTo[] = TEXT("c:\\a\\x\\y\\file"); if (!PathRelativePathTo(szOut, szFrom, FILE_ATTRIBUTE_DIRECTORY, szTo, FILE_ATTRIBUTE_NORMAL)) { handleError(); }</pre>		
Examples of Corrected Code	<pre>TCHAR szOut[MAX_PATH] = ""; // Buffer is correctly sized TCHAR szFrom[] = TEXT("c:\\a\\b\\path"); TCHAR szTo[] = TEXT("c:\\a\\x\\y\\file"); if (!PathRelativePathTo(szOut, szFrom, FILE_ATTRIBUTE_DIRECTORY, szTo, FILE_ATTRIBUTE_NORMAL)) { handleError(); }</pre>		
Source Reference	http://msdn.microsoft.com/library/default.asp? url=/library/en-us/shellcc/platform/shell/ reference/shlwapi/path/pathrelativepathto.asp²		
Recommended Resource			
Discriminant Set	Operating System • Windows		
	Languages • C • C++		

Cigital, Inc. Copyright

Copyright © Cigital, Inc. 2005-2007. Cigital retains copyrights to this material.

Permission to reproduce this document and to prepare derivative works from this document for internal use is granted, provided the copyright and "No Warranty" statements are included with all reproductions and derivative works.

For information regarding external or commercial use of copyrighted materials owned by Cigital, including information about "Fair Use," contact Cigital at copyright@cigital.com¹.

The Build Security In (BSI) portal is sponsored by the U.S. Department of Homeland Security (DHS), National Cyber Security Division. The Software Engineering Institute (SEI) develops and operates BSI. DHS funding supports the publishing of all site content.

PathRelativePathTo 3

^{1.} mailto:copyright@cigital.com